

Name: _____

Job Date: _____

Company: _____

Job Reference: _____

Cellular: _____

Roofing System: TPO PVC NDL Job: Yes No

Email: _____

If NDL, Rep Name: _____


Distributor: _____

Color: White Tan Gray Slate Gray Dark Bronze

Note: For multiple sizes and/or colors use additional quote forms. Want to fill out faster? Go online FlashCo.com/Edge-FlashForm

FLASHWRAP® - SPLIT BOOTS


Cylindrical Split Boot Qty: _____



Custom Size

A: Diam. _____ in.
 B: Height _____ in. (8" std.)
 C: Flange _____ in. (6" std.)
 Hose Clamp: Yes No


Square/Rect. Split Boot Qty: _____



Custom Size

A1: Tube: _____ in.
 A2: Tube: _____ in.
 B: Height _____ in. (8" std.)
 C: Flange _____ in. (6" std.)
 R: Radius _____ in. (1/8" std.)

Conical Split Boot Qty: _____




Custom Size

A: Top Dia. _____ in.
 D: Btm Dia. _____ in.
 B: Height _____ in. (8" std.)
 C: Flange _____ in. (6" std.)
 Hose Clamp: Yes No

FLASHJACK™ - CLOSED BOOTS

Cylindrical Boot Qty: _____




Custom Size

A: Diam. _____ in.
 B: Height _____ in. (8" std.)
 C: Flange _____ in. (6" std.)
 Hose Clamp: Yes No

Built to size

Square/Rect. Boot Qty: _____




Custom Size

A1: Tube: _____ in.
 A2: Tube: _____ in.
 B: Height _____ in. (8" std.)
 C: Flange _____ in. (6" std.)
 R: Radius _____ in. (1/8" std.)

Built to size

Conical Boot Qty: _____




Custom Size

A: Top Diam. _____ in.
 D: Btm Diam. _____ in.
 B: Height _____ in. (8" std.)
 C: Flange _____ in. (6" std.)
 Hose Clamp: Yes No

FLASHDRAIN™ - DRAINS

Scupper Qty: _____




Custom Size

W: Width _____ in.
 H: Height _____ in.
 D: Depth _____ in.
 Throughwall Overflow

Type: Center R. Corner L. Corner

FLASHACCESSORY™ - ACCESSORIES

Sealant Pocket Qty: _____




Custom Size

W: Width _____ in.
 L: Length _____ in.
 H: Height _____ in. (2" std.)

Split side is along L

Curb Wrap Configuration Qty: _____




Configuration

2 pcs 4 pcs
 Split Closed
 A: Dim. _____ in.
 B: Dim. _____ in.
 H: Height _____ in. (8" & 12" std.)
 F: Flange _____ in. (6" std.)

FLASHEDGE™ - COATED METAL

Drip Edge Qty: _____




Options

No Hem
 Hem Open
 Hem Closed
 Hem Return _____ in.

Size
 A= _____ in.
 B= _____ in.
 C= _____ deg.

Gravel Stop Drip Edge Qty: _____




Options

No Hem
 Hem Open
 Hem Closed
 Hem Return _____ in.

Size
 A= _____ in.
 B= _____ in.
 C= _____ in.

Cleat Qty: _____



Cleat fits in Open Hem

Size
 C1= _____ in.
 C2= _____ in.
 C3= _____ in.

Cap Metal Qty: _____




Options

No Hem
 Hem Open
 Hem Closed
 Hem Return _____ in.

Size
 A= _____ in. B= _____ in. C= _____ in.

Z Bar Qty: _____




Size

A= _____ in.
 B= _____ in.
 C= _____ in.

Coated Side: E F

Roof To Wall/Starter Qty: _____



Size

A= _____ in.
 B= _____ in.
 C= _____ deg.

Coated Side: E F