

Name: _____

Job Date: _____

Company: _____

Job Reference: _____

Cellular: _____

Roofing System: TPO PVC NDL Job: Yes No

Email: _____

If NDL, Rep Name: _____


Contractor: _____

Color: White Tan Gray Slate Gray Dark Bronze

Note: For multiple sizes and/or colors use additional quote forms. Want to fill out faster? Go online FlashCoMfg.com/Distributor-FlashForm


FLASHWRAP® - SPLIT BOOTS

Cylindrical Split Boot Qty: _____




Custom Size
 A: Diam. _____ in.
 B: Height _____ in. (8" std.)
 C: Flange _____ in. (6" std.)
 Hose Clamp: Yes No

Square/Rect. Split Boot Qty: _____



Custom Size
 A1: Tube: _____ in.
 A2: Tube: _____ in.
 B: Height _____ in. (8" std.)
 C: Flange _____ in. (6" std.)
 R: Radius _____ in. (1/8" std.)


Conical Split Boot Qty: _____



Custom Size
 A: Top Dia. _____ in.
 D: Btm Dia. _____ in.
 B: Height _____ in. (8" std.)
 C: Flange _____ in. (6" std.)
 Hose Clamp: Yes No

FLASHJACK™ - CLOSED BOOTS


Cylindrical Boot Qty: _____



Custom Size
 A: Diam. _____ in.
 B: Height _____ in. (8" std.)
 C: Flange _____ in. (6" std.)
 Hose Clamp: Yes No

Built to size


Square/Rect. Boot Qty: _____



Custom Size
 A1: Tube: _____ in.
 A2: Tube: _____ in.
 B: Height _____ in. (8" std.)
 C: Flange _____ in. (6" std.)
 R: Radius _____ in. (1/8" std.)

Built to size


Conical Boot Qty: _____



Custom Size
 A: Top Diam. _____ in.
 D: Btm Diam. _____ in.
 B: Height _____ in. (8" std.)
 C: Flange _____ in. (6" std.)
 Hose Clamp: Yes No

FLASHDRAIN™ - DRAINS


Scupper Qty: _____



Custom Size
 W: Width _____ in.
 H: Height _____ in.
 D: Depth _____ in.
 Throughwall Overflow
 Type: Center R. Corner L. Corner


FLASHACCESSORY™ - ACCESSORIES

Sealant Pocket Qty: _____



Custom Size
 W: Width _____ in.
 L: Length _____ in.
 H: Height _____ in. (2" std.)
 Split side is along L


Curb Wrap Qty: _____



Configuration
 2 pcs 4 pcs
 Split Closed
 A: Dim. _____ in.
 B: Dim. _____ in.
 H: Height _____ in. (8" & 12" std.)
 F: Flange _____ in. (6" std.)

FLASHEDGE™ - COATED METAL


Drip Edge Qty: _____



Options
 No Hem
 Hem Open
 Hem Closed
 Hem Return _____ in.

Size
 A = _____ in.
 B = _____ in.
 C = _____ deg.


Gravel Stop Drip Edge Qty: _____



Options
 No Hem
 Hem Open
 Hem Closed
 Hem Return _____ in.

Size
 A = _____ in.
 B = _____ in.
 C = _____ in.


Cleat Qty: _____



Size
 C1 = _____ in.
 C2 = _____ in.
 C3 = _____ in.

Cleat fits in Open Hem


Cap Metal Qty: _____



Options
 No Hem
 Hem Open
 Hem Closed
 Hem Return _____ in.


Size
 A = _____ in. B = _____ in. C = _____ in.

Z Bar Qty: _____



Size
 A = _____ in.
 B = _____ in.
 C = _____ in.
 Coated Side: E F

Roof To Wall/Starter Qty: _____



Size
 A = _____ in.
 B = _____ in.
 C = _____ deg.
 Coated Side: E F

Indicate Pitch or Angle if not 90°