

# FlashVent™ T-TOP VENT

PVC Low Slope Systems

## OVERVIEW

FlashCo's FlashVent T-Top Roof Vents are prefabricated exhaust vents used for non-heated exhaust ventilation. FlashCo T-Tops are designed for most single ply low slope roofing systems, eliminate field fabrication, and install in minutes. The strong galvanized steel sub-base meets the minimum 8" height requirement typically specified on low slope roofing systems.

FlashCo's T-Top PVC flashing is factory welded reinforced membrane and has a three-inch weldable flange. The T-shaped hood is made of SMP painted steel, closely matching the color of the PVC, and is designed with ends or "ears." T-Top vents are not for use in dryer exhaust applications, instead FlashCo recommends its EasyFlapper™ for dryer vent applications. All T-Top vents come standard with an 1/8" galvanized wire mesh, and are available in three standard sizes: 4", 6", 8" and boxed.

## INSTALLATION

FlashCo's FlashVent T-Top Vent shall be installed in accordance with the recommendations and specifications of the roofing material manufacturer or architect.

1. Place appropriately sized T-Top over vent hole in the roof deck.
2. Lift membrane flange and fasten sub-base to deck.
3. Heat weld membrane flange to deck membrane.



## FEATURES AND BENEFITS

- Eliminates field fabrication
- T-Top ends block wind thereby allowing exhaust
- Insect screen keeps bugs out of vent
- Reduces installed and labor costs

## SAVING THE CONTRACTOR TIME

- **FlashCo's Brand Promise is Speed:** shipping 90% of orders within 3 days.
- 24/7/365 Online Contractor Portal and additional time-saving tools
- Most orders delivered on FlashCo's own delivery trucks
- Get off the roof sooner

## SIZES, PACKAGING, MATERIALS & COLORS

Size	Qty/Box	Wt./Box	Material	Colors
4"	6 ea.	8 lbs.	60 mil Reinforced TPO	White, Gray, Tan, Slate Gray, Dk. Bronze
6"	4 ea.	10 lbs.	60 mil Reinforced TPO	White, Gray, Tan, Slate Gray, Dk. Bronze
8"	2 ea.	12 lbs.	60 mil Reinforced TPO	White, Gray, Tan, Slate Gray, Dk. Bronze

